

TGBT4N

4 Hour Electronic Boost Timer

Features & Benefits

- Automatic timer countdown selection for up to 4 hours.
- Typical applications such as immersion heaters, room heaters, towel rails and lighting.
- Fits a standard flush or surface mount BS wall box min. 25mm deep.



Technical Data

Operating Voltage	230V AC
Frequency	50Hz
Installation Type	Surface
Earth Class Rating	Class II
Operating Temperature	0°C to 45°C
Ingress Protection Rating	IP20
Setting Type	Button Press
Back Box Minimum Depth (mm)	25
Push Buttons	Yes (Boost Button)
Mounting Hole Centres (mm)	60
Standby Consumption	<1W
Number Of Channels	1
Switch Rating	13A Resistive, 100W LED, 1000W Halogen, 500W Fluorescent
Shortest Switching Time	15 Minutes

Data sheet

TGBT4N

Time / Immersion & General Purpose Timeswitches

Time Delay Range	15 Minutes to 4 Hours (¼ Hour, ½ Hour, 1 Hour, 2 Hours and 4 Hours)
Permanent ON Facility	No
Multiple Unit Support	No

General

Weight (g)	113
Height (mm)	85
Width (mm)	85
Depth (mm)	31
Body Construction	Polycarbonate
Product Colour	White
Accessories (Included)	Screws
EAN Number	5012483015186
Guarantee Period	3 Years
Trade Tariff Commodity Code	8536508090

Line Diagrams

