


JC50313

IP65 Emergency Bulkhead Self-Test




Maintained IP65 exit bulkhead with self-test




Distance from wall (parallel)

Mounting height	Distance
2.0m	3.49m
2.5m	3.93m
3.0m	4.20m
3.5m	4.33m
4.0m	4.45m




Distance from wall (adjacent)

Mounting height	Distance
2.0m	3.97m
2.5m	4.45m
3.0m	4.59m
3.5m	4.88m
4.0m	4.93m



Distance from adjacent fitting (parallel)

Mounting height	Distance
2.0m	8.18m
2.5m	9.22m
3.0m	10.17m
3.5m	11.07m
4.0m	11.69m



Distance from adjacent fitting (series)

Mounting height	Distance
2.0m	9.91m
2.5m	10.43m
3.0m	11.61m
3.5m	12.51m
4.0m	12.91m



7W LED



RATED



COL TEMP.



397 LUMENS



CRI: RA

Luminous flux	397 lm
Correction factor	1.00
Emergency lighting factor	1.00
Emergency lighting luminous flux	397 lm

Light output ratio	100.00
Light output ratio (lower hemisphere)	100.00
Light output ratio (upper hemisphere)	0.00

The spacing table is based on the following parameters:
 Maintenance factor: 0.72 | Emergency lighting factor: 1.00
 Minimum illuminance on centre line: 1.00 lx | Minimum illuminance on half of escape route width: 0.50 lx
 Diversity on the centre line max. 40: 1 | Width of escape route: 2.00 m