





Tring RGBW Floodlights



10W, 20W, 30W & 50W



STOP

READ THESE INSTRUCTIONS THOROUGHLY BEFORE INSTALLATION KEEP THESE INSTRUCTIONS FOR FUTURE REFERENCE.


IMPORTANT:
This product must be installed by a qualified electrician or competent person, and in accordance with current building and IET wiring regulations.

BOX CONTENTS

This lighting fixture has been properly packed to avoid damage during transit. Before commencing with the installation carefully inspect the luminaire to confirm there is no damage. DO NOT INSTALL if any damage has occurred to the fixture or any of its components.

- Light Fitting
- Instruction Manual
- Fixing Kit

TOOLS REQUIRED



- Drill
- 5mm Hex Key
- Cable

INSTALLATION INSTRUCTIONS

1

2

3

4

Electrical connection wiring

- LIVE (L) = Brown
- Earth (⊕) = Yellow/Green
- NEUTRAL (N) = Blue

5

PLEASE READ THESE INSTRUCTIONS BEFORE INSTALLATION.

WARNING: Risk of electric shock! Isolate the mains power before proceeding.

- Turn off the mains power before performing inspections, installation, or removal
- Verify that the supply voltage is correct by comparing it with the luminaire label information
- It is the installers responsibility to ensure installation is suitable for the total load of the luminaire(s). The supply cable, fuses/circuit breakers must be correctly rated for the electrical load and considering for any transient inrush currents that may occur
- Do not perform insulation strength or resistance tests on installed luminaire(s) connected

1. Disconnect mains supply
2. Detach adjustable bracket from the light fitting and fix to the desired surface. Re-attach the bracket
3. Adjust the angle to suit and tighten bracket screws. **IMPORTANT:** make sure to not exceed the angle shown
4. Connect wires as shown and then reconnect mains supply and test
5. Remote control operation



Manby Business Park, Manby, Lincolnshire, LN11 8UT
Lumineux is a B&T Associates Ltd company.

Technical Helpline: +44 (0)1507 328031

www.lumineux.co.uk

TRING FLOODLIGHT DIMENSIONS


DISPOSAL

Disassembly instructions for end of life disposal available on website.

Disposal of Electronic Equipment WEEE Directive 2002/96/EC This product falls within the scope of the Waste Electrical & Electronic Equipment Directive (WEEE), which means the product should not be disposed of as normal household waste. Please recycle where facilities exist or check with your Local Authority. RoHS - All components and materials used in this product are RoHS 2002/95/EC compliant.

Specifications may change from time to time. The information contained in this leaflet is for guidance only and should not be considered as always accurate and should be treated as not representative.

Part No.	Description	Watts	L (mm)	W (mm)	H (mm)	Weight
430013	Tring RGBW	10W	115	102	25	0.23Kg
430014	Tring RGBW	20W	133	150	29	0.36Kg
430015	Tring RGBW	30W	157	180	32	0.56Kg
430016	Tring RGBW	50W	205	233	40	0.93Kg



WARRANTY

This luminaire is warranted for a period of 3 years from the date of purchase.** The warranty could be invalidated should the light fitting not be installed according to these instructions, outside the scope of the specification or the product has been altered or tampered with in any way. Please see website for terms and conditions.

PRODUCT TEMP SPECIFICATION

Standard -20°C to +30°C

Installation Engineers Contact Details:		Luminaire Reference / Location
Name:	Tel:	

This product contains a light source of energy efficiency Class G.